

Dry stoner

type RS 3P | 7P | 2-7P | 2-15P



RS 2-15 P

- Effective separation of stones or other foreign materials from dry, loose or grainy materials
- 4 different sizes
- Low power consumption
- No rotating parts
- Viewing window for quick control
- Adjustable for various kinds of grain
- Machine and frame made of steel
- Machine cover made as a self-supporting glass laminated shell
- Oscillating suspended sieve
- Continuous screen inclination
- Vibration power unit with inclination adjustment

Technical data

		RS 3P	RS 7P	RS 2-7P	RS 2-15P
Capacity (wheat)	t/h	3.0	7.0	7.0	15.0
Net weight	kg	190	230	450	662
Voltage	V	3 x 400/230 – 50 Hz			
Power consumption	kW	0.25	2 x 0.25	2 x 0.25	2 x 0.55
Capacity	t/h	1 – 1.5	3 – 3.5	3 – 3.5	7.5 – 10
Rated current	A	0.78		2 x 1.45	
Vibration unit – adjustable		30° – 70°			
Slant screen – adjustable		4 – 9°		2 – 15°	
Air regulation flap – adjustable		0° – 90°			
Noise level around the machine and in the operator's post	dB(A)	< 85			
Minimum and maximum surrounding temperature		-20°C / +40°C			
Built-up space	m³	2.72	4.27	4.27	6.10
Max. pressure loss	pa	1,200	1,200	1,200	1,200
Aspiration air requirement	m³/min	45	80	90	140